



598 Patterson Blvd., Pleasant Hill, CA USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for Flood Light 12W Square

Issued on: 1/4/2008

Revised on: 3/10/2010

1. Specs

Optical Specs	Warm White	Cool White
LED Efficiency	>60.9Lm/W	>87Lm/W
Drivers	External listed waterproof power supply	
Luminous Flux	>#Lm	
LED Colors	RGB (4 Red, 4 Green, 4 Blue) AWB (4 Amber, 4 White, 4 Blue) Wht (12 White)	
Beam Angle	60° / 30°	
Electrical Specs		
Input Voltage & Frequency	DC24V 50-60Hz	
Max Power Consumption	15W	
Energy Consumption Per Year	#Kw/Hr	
Operating Current		
Light Source	#W	
Control Mode	DMX 512 Console	
Other Specs		
Operating Temperature	-30°C - +45°C (-22°F - +113°F)	
Operating Humidity	10 - 90 RH	
Storage Temperature	-20°C - +45°C (-4°F - +113°F)	
Dimensions	4.8"H x 6.7"W x 12"L (123mmH x 170.5mmW x 300mmL)	
Fabrication Material	Aluminum Alloy & Glass	
Net Weight	4.0±1.1lbs (4.0±0.5kg)	
Lifespan	50,000 Hours	
Warranty	3 Years	