



598 Patterson Blvd., Pleasant Hill, CA USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for Flood Light 90W

Issued on: 1/4/2008

Revised on: 3/10/2010

1. Specs

Optical Specs	Warm White	Cool White
LED Efficiency	>60.9Lm/W	>87Lm/W
Drivers	External listed waterproof power supply	
LED Colors	RGB (12 Red, 12 Green, 12 Blue) * 2.4W AWB (12 Amber, 12 White, 12 Blue) * 2.4W Wht (36 White) * 2.4W	
Beam Angle	60° / 30°	
Electrical Specs		
Input Voltage & Frequency	DC24V 50-60Hz	
Max Power Consumption	105W	
Control Mode	DMX 512 Console	
Other Specs		
Operating Temperature	-30°C - +45°C (-22°F - +113°F)	
Operating Humidity	10 - 90 RH	
Storage Temperature	-20°C - +45°C (-4°F - +113°F)	
Dimensions	5.8"H x 7.7"W x 23.7"L (148mmH x 196mmW x 601mmL)	
Fabrication Material	Aluminum Alloy & Glass	
Net Weight	5.0±1.1lbs (5.0±0.5kg)	
Lifespan	50,000 Hours	
Warranty	3 Years	